



立得精密科技有限公司
LEADER PRECISION MACHINERY CO., LTD.



RH-45

**MULTI-FUNCTION
MOVING COLUMN
MACHINING CENTER**

多功能動柱式切削中心機

Specifications

型號 / Model	Unit	RH-45	
Controller	NC controller	M70-2B(OP:0i-MD)	
	Spindle motor-cont/30min	KW	11/15
	Axis feed motor-X/Y/Z	KW	7 / 4.5 / 4.5B
Spindle	Taper		BT 40
	Type		5GT Belt
	Speed	RPM	8000(OP:10000)
Travel	X	MM	4500 (OP:2500~8000)
	Y/Z	MM	610
	Spindle nose to table surface	MM	150~760
Feed rate	Rapid feed rate-X/Y/Zvv	M/min	24/20/20
	Cuting feedrate by table	M/min	8
Accuracy	X Rack	MM	±0.04
	X Ballscrew(OP)	MM	±0.02
	Y/Z Ballscrew	MM	±0.01
	Repeatability	MM	X : ±0.015(±500) Y/Z :±0.01
Table	Table work area	MM	600*4500(OP:2500~8000)
	Dimension of T-slot		T18/4/125
	Max.table load	KG	200 (500MM)
Tools	Magazine capacity	T	24
	Magazine type		Tool chain
	Max. tool length/diameter	MM	200/80
	Max. tool weight	KG	7
Machine	Coolant tank capacity	L	200
	Min./Max. air pressure	kg/cm ²	6
	Power requirement	KVA	40

L102003-201707



LEADER PRECISION MACHINERY CO., LTD
 No.385, LN.549, SEC 2, SANFENG RD., FENGYUAN DIST, TAICHUNG CITY 420, TAIWAN (R.O.C)
 | 立得精密科技有限公司 | 台中市豐原區三豐路2段549巷385號

• Tel:+886-4-25228339
 • Fax:+886-4-25223550

• E-mail:leader.cnc@msa.hinet.net
 • <http://www.leader-machine.com.tw>